

HAKO-C158 Mini-ITX Enclosure

Feature:

- 1. Design for most Mini-ITX motherboards.
- 2. Easy system integration.
- 3. Low noise and light weight.
- 4. Solid and stable with quality design.





Front Panel	Power switch x 1.Power LED x 1.HDD LED x 1.
Right Side	 USB Port x 2. Audio IN/OUT x 1. Optical drive support slime ODD x 1. Compact flash slot(not include module)
Back Panel	 Standard I/O shield (not included). DC Jack x 1. Expansion PCI/PCI-E slot x 1. Extra serial port x 3.
Internal Structure	 4cm system cooling x 1. Standard memory height. 3.5" HDD x 1 or 2.5" HDD x 1.
Dimension (WxDxH)	12.0 x 10.6 x 2.3 inch (306.0 x 269.9 x 59.5 mm)
Material	Cold rolled steel and extruded aluminum front panel
Surface	Aluminum front panel with anodized finish; Black wet paint with texture coat.
Colour	Black. Customizable colour.


Power Solutions:

Internal Power Supply	External AC adapter	
C7 (80W) DC Power Board	60 Watts (12V) or 80 Watts (12V)	
C9 (120W) DC Power Board	90 Watts (19V) or 120 Watts (19V) or 120 Watts (24V)	
C4 (120W) DC Power Board	90 Watts (19V) or 120 Watts (19V)	
M2 (160W) Automotive DC Power Board		









UNIT:mm

E-mail: sales@kiwatek.com Website: www.kiwatek.com