

## ONDO-F546 Fanless Enclosure


## Feature:


- 1. For Mini-ITX board with CPU TDP 65W max.
- 2. Support 3 x expansion slot for PCle or PCl
- 3. 4 x DB9 ports on rear I/O
- 4. Adjustable heat pipe provides excellent compatibility


## Specifications:

Front Panel	<ul> <li>Power switch x 1.</li> <li>Power LED x 1.</li> <li>HDD LED x 1.</li> <li>USB 2.0 Port x 2.</li> </ul>	
Back Panel	<ul> <li>Standard I/O shield (not included).</li> <li>Expansion slot x 3.</li> <li>DB9 port x 4.</li> </ul>	
Internal Structure	<ul><li>Standard memory height.</li><li>2.5" HDD x 2.</li><li>3.5" HDD x 1.</li></ul>	
Dimension (WxDxH)	9.57 x 10.55 x 6.89 inch ( 243.0 x 268.0 x 175.0 mm )	
Material	SPCC with nickel electroplating Brushed and anodized aluminum panel	
Surface	Black wet paint with texture coat.	










## Power Solutions:

Internal Power Supply	External AC adapter
C4 (150W) DC Power board	90 or 120 Watts (19V)



**UNIT:mm** 

E-mail: sales@kiwatek.com Website: www.kiwatek.com